


REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	09/15/2021	



NOTES:

1. RoHS Compliant
2. Levels of protection: IP68
3. Cable: UL2517,PVC/PUR,Black
4. Operating temperature: -25℃~85℃
5. Company Logo
6. Connector tolerances:


		linear dimension										
variable range	tolerance	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all to 5	over 5 to 30	over 30 to 120	over 120 to 160	
	±0.15	±0.25	±0.35	±0.55	±0.80	±1.05	±1.30	0.5	0.025	0.06	0.12	0.4

7. Cable length tolerance:


- 01~03m: ±50mm
- 04~06m: ±75mm
- 07~10m: ±100mm
- 11~20m: ±200mm
- 21~30m: ±300mm
- 31~99m: ±500mm

S5M-M12T - XXP - FF-SL8AXX - 00AH
 Coding: A,B,D,X,T
 Cable length: 01: 01Meter, 02: 02Meters, 99: 99Meters
 Standard

4	Black	4	Black
3	Blue	3	Blue
2		2	Whitr
1	Brown	1	Brown
PIN	WIRE	PIN	WIRE



3P



4P

Remark: This drawing is a controlled document for Cymanu. All specifications are subject to change without prior notice.

SIZE: A4	SCALE: 4:3	CHECKED: C. LU	DATE: 09/15/2021
UNIT: mm	SHEET: 1/1	APPROVED: H. JIANG	DATE: 09/15/2021

PARAM: K. ZHAO	DATE: 09/15/2021	PART NO: S5M-M12T-XXP-FF-SL8AXX-00AH
TITLE: M12T female,Front Fastened Socket	DATE: 09/15/2021	CUSTOMER:

Cymanu 囍字電子
 NINGBO CHANGTU ELECTRONICS MANUFACTURING CO., LTD
 Email: sales@cymanu.com WWW.CYMANU.COM