





REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	08/17/2021	

NOTES:

1. RoHS Compliant
 2. Levels of protection: IP67
 3. Installation mode: Solder, Front fastened
 4. Operating temperature: -40°C~105°C
 5. Applicable Panel: Panel Hole
- For Panel Thickness Max: 4.5mm

6. Connector tolerances:

variable range	linear dimension										≡	□	∥	⊥	
	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all	over 5 to 30	over 30 to 120	over 120 to 200					
tolerance	±0.15	±0.25	±0.35	±0.55	±0.80	±1.05	±1.30	0.5	0.025	0.06	0.12	0.4			



Remark: This drawing is a controlled document for Cymannu. All specifications are subject to change without prior notice.

SIZE: A4	SCALE: 4 : 3	CHECKED: C. LU	DATE: 08/17/2021	DRAWN: K. ZHAO	DATE: 08/17/2021	PART NO.: SSD-M12D-XXP-MM-SL7001-00AH	
UNIT: mm	SHEET: 1 / 1	APPROVED: H. JIANG	DATE: 08/17/2021			TITLE: M12D male Front Fastened Socket	

NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD
Email: sales@cymannu.com WWW.CYMANNU.COM