




REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	08/17/2021	



NOTES:

1. RoHS Compliant
2. Levels of protection: IP67
3. Installation mode: Solder
4. Operating temperature: -40 °C~105 °C
5. Connector tolerances:

linear dimension	≡	—	□	//	⊥	
variable range	to	over	to	over	to	
10	18	30	50	80	120	
30	50	80	120	160	all	
50	80	120	160	to	5	
80	120	160	to	30	5	
120	160	to	0.025	0.06	0.12	
160	to	0.5	0.025	0.06	0.12	
tolerance	±0.15	±0.25	±0.35	±0.58	±0.80	±1.05
	±1.30	0.5	0.025	0.06	0.12	0.4

5PM-M12D - XXP - MM-SL7000 - 00AH

Coding: A,B,D

Poles

Standard

Remark: This drawing is a controlled document for Cymannu. All specifications are subject to change without prior notice.

SIZE:	SCALE:	CHECKED:	DATE:	PART NO.:
A4	4 : 3	K. ZHAO	08/17/2021	5PM-M12D-XXP-MM-SL7000-00AH
UNIT: mm	SHEET:	APPROVED:	DATE:	CUSTOMER:
1 / 1	1 / 1	H. JIANG	08/17/2021	M12D male Plug Solde

Cymannu 囍字電子
NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD
Email: sales@cymannu.com WWW.CYMANNU.COM