




REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	08/17/2021	



- NOTES:
1. RoHS Compliant
  2. Levels of protection: IP67
  3. Installation mode: Solder
  4. Operating temperature: -40°C~105°C
  5. Connector tolerances:

variable range	linear dimension										≡	□	∥	L
	over 18 to 10	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 180	all	to 5	over 5 to 30	over 30 to 120				
tolerance ±0.15	±0.25	±0.35	±0.55	±0.80	±1.05	±1.30	0.5	0.025	0.06	0.12	0.4			

SPM-M12D - XXP - FF-SL7000 - 00AH  
 Coding: A,B,D  
 Poles  
 Standard

Remark: This drawing is a controlled document for Cymannu. All specifications are subject to change without prior notice.

SIZE: A4	SCALE: 4 : 3	DRAWN: K. ZHAO	DATE: 08/17/2021
UNIT: mm	SHEET: 1 / 1	CHECKED: C. LU	DATE: 08/17/2021
		APPROVED: H. JIANG	DATE: 08/17/2021

PART NO: SPM-M12D-XXP-FF-SL7000-00AH
TITLE: M12D female Plug Solde
CUSTOMER:

**Cymannu** 囍字電子  
 NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD  
 Email: sales@cymannu.com WWW.CYMANNU.COM