



REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	10/21/2021	/

NOTES:


1. RoHS Compliant
 2. Levels of protection: IP67
 3. Installation mode: Solder, Front fastened
 4. Operating temperature: -40°C~105°C
 5. Applicable Panel: Panel Hole
- For Panel Thickness Max: 4.5mm

6. Connector tolerances:

variable range	linear dimension										≡	□	∥	⊥	
	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all	over 5 to 30	over 30 to 120	tolerance					
to 10	±0.15	±0.25	±0.35	±0.55	±0.80	±1.05	±1.30	0.5	0.025	0.06	0.12	0.4			



S5D-M8B - XXP - MM-SL7000 - 00AH
 Coding: A,B
 Poles
 Standard



Panel Hole

Remark: This drawing is a controlled document for Cymannu. All specifications are subject to change without prior notice.

SIZE:	SCALE:	CHECKED:	DATE:	DATE:	DATE:
A4	4 : 3	K. ZHAO	10/21/2021	10/21/2021	10/21/2021
UNIT: mm	SHEET: 1 / 1	APPROVED: H. JIANG			

PART NO.:	TITLE:	CUSTOMER:
S5D-M8B-XXP-MM-SL7000-00AH	M8B male, Front Fastened Socket	/

Cymannu 囍字电子
 NINGBO CHANGTU ELECTRONICS MANUFACTURING CO., LTD
 Email: sales@cymannu.com WWW.CYMANNU.COM