


REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	10/21/2021	/




- NOTES:
1. RoHS Compliant
 2. Levels of protection: IP68
 3. Cable: UL2517,PVC/PUR,Black
 4. Operating temperature: -25℃~85℃
 5. Company Logo
 6. Connector tolerances:

variable range	linear dimension											
	over 18 to 10	over 30 to 30	over 50 to 50	over 80 to 80	over 120 to 120	over 160 to 160	all to 5	over 5 to 30	over 30 to 120	over 120 to 120		
tolerance	±0.15	±0.25	±0.35	±0.55	±0.80	±1.05	±1.30	0.5	0.025	0.06	0.12	0.4

7. Cable length tolerance:

- 01~03m: ±50mm
- 04~06m: ±75mm
- 07~10m: ±100mm
- 11~20m: ±200mm
- 21~30m: ±300mm
- 31~99m: ±500mm



99: 99Meters

Remark: This drawing is a controlled document for Cymannu. All specifications are subject to change without prior notice.

SIZE: A4	SCALE: 4 : 3	CHECKED: C. LU	APPROVED: H. JIANG
UNIT: mm	SHEET: 1 / 2	DATE: 10/21/2021	DATE: 10/21/2021

PART NO: SPM-M8A-XXP-MM-SL8AXX-00AH	TITLE: M8A male, Plug
CUSTOMER: /	

Cymannu 囍字電子

NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD
 Email: sales@cymannu.com WWW.CYMANNU.COM

