


PG9:
5SD-M12B-05P-FF-SH7000-00AH

M16*1.5:
5SD-M12B-05P-FF-SH7001-00AH




Installation shell opening: maximum thickness 4.5mm,
Installation torque 1.25Nm

Remarks: Pollution Level (3)/Overvoltage Category (II)/
Material Group (I)

Number of Positions	5P
Coding	
Current/Voltage	4A/60V
Voltage Proof	1.0kV
Rated Impulse Voltage	1.5kV



REV	ECN	SIGN	DATE	DESCRIPTION
1.1	V1	K. ZHAO	2024/12/27	Drawing update parameters



Technical Parameter:

- 1.Insulation Resistance: $\geq 100M\Omega$
- 2.Contact Resistance: $\leq 10m\Omega$
- 3.Durability: ≥ 100 cycles
- 4.Locking Torque: 0.4Nm
- 5.Compliant with RoHS
- 6.Protection Level: IP68
(1 meter water depth, 24 hours); IP69K
- 7.Temperature Range: $-25^{\circ}C \sim 85^{\circ}C$

5SD-M12B - 05P - FF-SH7001 - 00AH

Coding: A,B,D Thread type: 000: PG9
Poles 001: M16*1.5 Standard

	linear dimension							≡	—	□	//	⊥
variable range	to 10	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all	to 5	over 5 to 30	over 30 to 120	over 120 to
tolerance	±0.15	±0.25	±0.35	±0.45	±0.60	±0.75	±0.90	0.5	0.025	0.06	0.12	0.4

Remark: This drawing is a controlled document for Cymanu. All specifications are subject to change without prior notice.

		DRAWN: K. ZHAO	DATE: 08/10/2021	PART NO: 5SD-M12B-05P-FF-SH7001-00AH	 NINGBO CHANGYU ELECTRONICS MANUFACTURING CO., LTD Email: sales@cymanu.com WWW.CYMANU.COM
SIZE: A4	SCALE: 4 : 3	CHECKED: T. Pan	DATE: 08/10/2021	TITLE: M12B, Female, front-end installation	
UNIT:mm	SHEET: 1 / 1	APPROVED: H. JIANG	DATE: 08/10/2021	CUSTOMER:	