




REV	ECN	SIGN	DATE	DESCRIPTION
1.0	V0	K. ZHAO	07/01/2024	

PLR (Separately packaged)






NOTES:

- 1.Rate Current:13A
- 2.Rate Voltage:250V
- 3.Dielectric voltage withstand: 1500V
- 4.Wire range :14~20AWG;0.5~2.0mm²
- 5.Pitch :5.46mm, Poles : 4 P
- 6.Temperature Range: -55℃~125℃
- 7.Protection degree:IP68(1meter deep water, lasting for 24 hours);IP69K
- 8.RoHS Compliance
- 9.

CONTACT SIZE	INSULATION SIZE	WIRE RANGE
16	2.24-3.68 mm	14-20 AWG


Material:

- 1.Housing: PA66 GF, UL94V-0
- 2.PLR: PA66 GF ,UL94V-0, GREEN
- 3.Interface Sed: VMQ,ORANGE
- 4.Cable Seal: VMQ,ORANGE



PART NUMBER CHART

NUMBER	COLOR
63CT0604S3310B	GREY
63CT0604S2210B	BLACK
63CT0604S4310B	GREEN
63CT0604S8310B	BROWN



linear dimension										≡	—	□	//	⊥
variable range	to 10	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	all	to 5	over 5 to 30	over 30 to 120			
	tolerance	±0.15	±0.25	±0.35	±0.45	±0.60	±0.75	±0.90	0.5	0.025	0.06	0.12	0.4	

Remark: This drawing is a controlled document for Cymanu. All specifications are subject to change without prior notice.

	SIZE:	DRAWN:		DATE:		PART NO:
	A4	SCALE: 1 : 1	CHECKED: T. Pan	DATE: 07/01/2024	07/01/2024	
UNIT: mm		SHEET: 1 / 12	APPROVED: H. JIANG	DATE: 07/01/2024		CUSTOMER:

63CT0604SY10B	
Auto Connector, 4 Position, Female	